



TL-1 Plastic Barrier



Features

- » Approved to NCHRP 350 TL-1 (NZTA minimum requirement)
- » Available for hire or purchase
- » Durable polyethylene plastic
- » Double wall knuckle design prevents breakage at hinge points
- » Hinge design allows for 30° pivoting at joints
- » 200mm fill hole with plastic cap
- » Temporary Plastic Water-filled Barrier
- » Plastic water release cap at bottom
- » Suitable for impact speeds up to 50kph
- » Fork lift slots for easy movement
- » Includes steel connecting pin allowing sections to be locked together
- » Screens available



Specifications

NCHRP 350 TL-1

- » Speed: 50kph
- » Height: 810mm
- » Width: (base) 460mm
- » Weight: (empty) 36kgs
- » Weight: (filled with water) 500kgs
- » Effective length: 1860mm
- » Overall length: 1960mm




More information on **TL-1 Plastic Barrier** can be found at www.cspacific.co.nz or call **0800 655 200**

Leading road side and barrier systems supplier

CSP PACIFIC

306 Neilson St, Onehunga,
PO Box 12 949, Penrose,
Auckland 1642, New Zealand
www.cspacific.co.nz



Columns



Multiplate



Retaining



Hire



Barriers



Traffic Control