



TL-2 Plastic Water Filled Barrier

The **TL-2 Plastic Water Filled Barrier** is made up of plastic units that when joined together, using a steel connector and filled with water, provide positive work zone barrier protection to temporary construction sites and other miscellaneous roadside activities and has been tested to meet the evaluation criteria of NCHRP 350 Test Level (TL-2).

The **TL-2 Plastic Water Filled Barrier** is also available for hire. This is an ideal solution for temporary roadside protection without having to invest in product you may not use again.

Advantages

- » Approved to NCHRP 350 TL-2
- » Available for hire or purchase
- » Durable polyethylene plastic
- » 200mm fill hole with plastic cap
- » Temporary Plastic Water Filled Barrier
- » Plastic water release cap at bottom
- » Suitable for impact speeds up to 70 kph
- » Suitable for roadside or median applications
- » Includes twin pin steel connecting pin allowing sections to be locked together
- » Can be dispatched in stacks of 15 units



Specifications

- » NCHRP 350 TL-2
- » Speed: 70 kph
- » Height: 870mm
- » Width (base): 450mm
- » Weight (empty): 50kgs
- » Capacity: 560 litres of water
- » Overall length: 2000mm



More information on **TL-2 Plastic Water Filled Barrier** can be found at www.csppacific.co.nz or call **0800 655 200**

Leading road side and barrier systems supplier

CSP PACIFIC

306 Neilson St, Onehunga,
PO Box 12 949, Penrose,
Auckland 1642, New Zealand
www.csppacific.co.nz



Columns



Multiplate



Retaining



Hire



Barriers



Traffic Control