



TYPICAL CURVED RAIL LAYOUT

NOTES:

1. APPROACH GRADING IS TO BE 10H, 1V OR FLATTER MAINTAIN FREE OF OBSTRUCTIONS.
2. A MINIMUM CLEAR AREA OF 22M X 6M TO BE PROVIDED BEHIND THE GUARDRAIL.
3. CLEAR AREA BEHIND GUARDRAIL TO BE 6H:1V OR FLATTER AND MAINTAINED FREE OF OBSTRUCTIONS.
4. NO WASHERS ARE TO BE USED WITH THE MUSHROOM HEAD BOLTS ON FACE OF RAIL.
5. THERE CAN BE UP TO 3 APEX POSTS DEPENDING ON MOST LIKELY IMPACT DIRECTIONS.
6. RAIL ON SHELF ANGLE AT ALL APEX POSTS.

306 Neilson Street,
 Onehunga, Auckland
 PO Box 12 949, Penrose
 Auckland, New Zealand
 Telephone 09-634 1239
 Facsimile 09-634 4525
 www.cspacific.co.nz



Copyright: This design, information and drawing remain the property of CSP Pacific and may not be used or copied without approval in writing from CSP Pacific.

RAIL ON A CURVE
 NUGUARD 31™ POST

ACCEPTED BY NEW ZEALAND TRANSPORT AGENCY

Drawn by	MY	Date	22-03-2013
Checked		Scale	A4 AS SHOWN
Reference No.			

Drawing no.	FX653	Rev. No.	0
-------------	-------	----------	---