



BarrierGuard 800



Features

- » Approved to NCHRP 350 TL-3 and TL-4
- » Available for hire or purchase
- » Deflection of 1.5 metre
- » Light weight: 1000m BarrierGuard 800 – 90 tonne, compared to 1000m concrete - 1000 tonne
- » Rapid deployment – up to 288 m/hr
- » Requires anchoring only at end of each run
- » Also suitable permanent applications
- » BarrierGuard 800 is the highest performing temporary worksite barrier available
- » Very low exit angle following vehicle impact
- » Up to 144 metres (none inverted) can be transported on one truck (concrete 36m)
- » Radius connections – able to achieve minimum 35 metre radius
- » Connects directly to the ABSORB 350 temporary or TAU II permanent crash cushion
- » Screens available

Specifications

NCHRP 350 TL-3 and TL-4

- » Galvanised steel finish
- » Length: 12m/unit
- » Height: 800mm
- » Width: (base) 540mm
- » Width: (top) 235mm
- » Weight: 1080kg/12metre section
- » Up to 180 metres can be moved on one truck
- » Up to 300 metres can be installed in one hour

More information on **BarrierGuard 800**
can be found at www.cspacific.co.nz or call **0800 655 200**

Leading road side and barrier systems supplier

CSP PACIFIC

306 Neilson St, Onehunga,
PO Box 12 949, Penrose,
Auckland 1642, New Zealand
www.cspacific.co.nz



Columns



Multiplate



Retaining



Hire



Barriers



Traffic Control